

WEIGHING SYSTEMS

- accuracy 0,1%
- protection IP65
- includes ring, shackles and hook
- rechargeable Ni-Cd batteries
- battery charger

MINI-LOAD

- capacity : 300, 500, ..., 10.000 kg
- display LCD, 4 digits (height 25 mm)
- options : LED, IR remote control, sum memory, heat shield, transportation case



EXCEL-LOAD

- capacity : 300, 500, ..., 10.000 kg
- inox housing, display LCD, 5 digits (height 25 mm)
- options : printer, LED, IR remote control, sum memory, heat shield, serial output RS232, setpoint with relay



MACRO-LOAD

- capacity : 3.200, 6.300, ..., 32.000 kg
- display LED, 5 digits (height 52 mm)
- options : inbuilt printer, IR remote control, sum memory, heat shield, LCD



TR-LOAD

- capacity: 2.000, 3.000, ..., 32.000 kg
- display LED, 5 digits (25-60 mm), remote control OFF/TARA
- options : inbuilt printer, IR remote control extra functions, sum memory, heat shield, LCD

OPTIONS AND SPECIAL APPLICATIONS

● 1. craneblock high capacity



● 3. inbuilt printer



● 2. protection mask



● 4. separate display with cable connection



● 5. heat shield for foundry



● 6. loadcell with separate display and remote control



● 7. separate display



● 8. separate display with printer and radiotransmission



● 9. summation + display

